

mesh opening (micron)	mesh count mesh/cm	weave	thread diam.(micron)	open surface (%)	thickness (micron)	weight (g/m2)
1080	7	PW	350	57	675	186
760	10	PW	250	56	450	160
700	10	PW	300	49	570	230
680	12	PW	150	67	260	69
580	12	PW	250	48	460	192
530	12	PW	300	40	580	277
515	14	PW	200	52	360	143
470	15	PW	200	50	380	154
420	15	PW	250	40	470	240
425	16	PW	200	46	380	164
405	18	PW	150	53	260	104
375	19	PW	150	51	260	110
350	20	PW	150	49	260	115
340	24	PW	120	67	220	88
270	24	PW	150	42	280	138
250	27	PW	120	46	230	100
225	29	PW	120	43	230	107
210	32	PW	100	45	180	82
195	34	PW	100	44	180	87
180	36	PW	100	42	180	92
200	39	PW	55	61	95	30
150	40	PW	100	36	190	103
150	43	PW	80	42	155	71
150	47	PW	64	50	120	48
140	47	PW	71	43	130	59
140	49	PW	64	47	120	50
135	49	PW	71	44	130	62
125	54	PW	64	44	122	54
105	59	PW	64	38	123	61
90	64	PW	64	33	125	66
98	62	PW	64	36	124	64
85	72	PW	55	38	102	55
75	77	PW	55	33	105	58
80	80	PW	45	41	80	41
70	90	PW	39	40	68	34
65	90	PW	45	34	82	46
60	100	PW	39	36	69	38
56	110	PW	35	38	62	34
52	110	PW	39	33	70	42
48	120	PW	35	33	63	37
44	120	PW	39	28	72	46
42	130	PW	35	30	58	40
36	140	PW	35	25	62	43
32	150	TW	35	23	64	46

Top Zeven b.v.

Wateringweg 34, 2031 EJ Haarlem, Netherlands,
tel +31(0)23 5319051, fax +31(0)23 5319065
filter@topzeven.com , www.topzeven.com